

# DEBORT

We DEBORT people devote ourselves to give you best Tyre and Rim solution.

## OUR FACTORY

Advanced Germany Technology and stick production control to make high quality products for you.



## LAWN&GARDEN TIRE

P332/P332A/P332B



Size	PR	Tube Type	Tread Pattern	Rim Size	DEPTH (MM)	Section Width	Overall Diameter	Max Load	Inflation Pressure
						mm	mm	LBS	PSI
4.10/3.50-4	2	TL	P332	3.25	3	99	269	230	24
4.10/3.50-4	4	TL	P332	3.25	3	99	271	350	50
4.8/4.00-8	2	TL	P332	3.75	3.5	119	421	435	20
4.8/4.00-8	4	TL	P332	3.75	3.5	119	421	670	42
11X4.00-4	2	TL	P332	3.25	3	105	273	215	22
11X4.00-4	4	TL	P332	3.25	3	105	273	330	46
11X4.00-5	2	TL	P332	3	3	102	276	210	22
11X4.00-5	4	TL	P332	3	3	102	276	325	46
13X5.00-6	2	TL	P332	4.5	3	128	311	295	20
13X5.00-6	4	TL	P332	4.5	3	128	316	440	40
13X5.00-6	6	TL	P332	4.5	3	128	316	525	46
13X5.00-6	2	TL	P332A	4.5	5	128	311	295	20
13X5.00-6	4	TL	P332A	4.5	5	128	316	440	40
13X6.50-6	4	TL	P332	5	3.5	160	333	460	28
15X6.00-6	2	TL	P332	4.5	6	155	363	365	14

15X6.00-6	4	TL	P332	4.5	6	160	380	570	30
15X6.00-6	6	TL	P332	4.5	6	160	385	595	45
15X6.50-8	4	TL	P332	5.375	6	156	381	565	28
16X6.50-8	2	TL	P332	5.375	7.1	165	403	415	14
16X6.50-8	4	TL	P332	5.375	7.1	165	410	620	28
16X6.50-8	6	TL	P332	5.375	7.1	167	415	785	42
16X7.50-8	2	TL	P332	5.375	7.1	182	405	475	12
16X7.50-8	4	TL	P332	5.375	7.1	182	410	680	24
16X7.50-8	6	TL	P332	5.375	7.1	182	415	900	36
18x6.50-8	4	TL	P332	5	4	165	455	770	28
18x7.00-8	4	TL	P332	5.375	7	177	450	785	26
18x7.00-8	6	TL	P332	5.375	7	177	460	990	36
18x8.50-8	2	TL	P332	7	7.1	210	450	515	10
18x8.50-8	4	TL	P332	7	7.1	210	455	815	22
18x8.50-8	4	TL	P332B	7	5.5	210	455	815	22
18x8.50-10	4	TL	P332	7	7.1	201	475	795	22
18X9.50-8	2	TL	P332	7	5	223	455	695	12
18X9.50-8	4	TL	P332	7	5	223	460	1040	24
18X9.50-8	6	TL	P332	7	5	223	465	1320	36
18x10.50-10	4	TL	P332	8.5	8.5	250	485	990	20
20X8.00-8	2	TL	P332	6.5	3.5	207	507	600	10
20X8.00-8	4	TL	P332	6.5	3.5	207	507	950	22
20X8.00-10	4	TL	P332	6	8	205	505	895	24
20X8.00-10	6	TL	P332	6	8	205	510	1200	35
20X10.00-8	2	TL	P332	6	7.1	240	485	750	10
20X10.00-8	4	TL	P332	7	7.1	240	500	1190	22
20X10.00-8	6	TL	P332	7	7.1	240	510	1545	34
20X10.00-10	4	TL	P332	8	8	243	508	1160	22
20X10.00-10	6	TL	P332	8	8	240	515	1245	36
22X9.50-12	4	TL	P332	7	7.1	225	560	1290	24
22X11.00-10	4	TL	P332	8.5	7.1	268	556	1480	22
23X8.50-12	4	TL	P332	7	9.8	206	580	1120	22
23X8.50-12	6	TL	P332	7	9.8	206	595	1445	34
23X9.50-12	2	TL	P332	7	5	232	580	920	12
23X9.50-12	4	TL	P332	7	5	232	595	1380	24
23X10.50-12	2	TL	P332	8.5	9.8	250	580	890	10
23X10.50-12	4	TL	P332	8.5	9.8	250	590	1340	20
23X10.50-12	6	TL	P332	8.5	9.8	250	595	1760	32
24X9.50-12	4	TL	P332	7	7.1	231	605	1500	24
24X12.00-12	4	TL	P332	10.5	9.8	295	605	1710	20
24X12.00-12	6	TL	P332	10.5	9.8	295	615	2260	32
24X12.00-12	8	TL	P332	10.5	9.8	293	610	2910	50
26X12.00-12	4	TL	P332	10.5	9.8	312	650	1780	20
26X12.00-12	6	TL	P332	10.5	9.8	310	655	2450	35
26X12.00-12	8	TL	P332	10.5	9.8	310	655	3020	50

# LAWN&GARDEN TIRE P508



Size	PR	Tube Type	Tread Pattern	Rim Size	DEPTH (MM)	Section Width	Overall Diameter	Max Load	Inflation Pressure
						mm	mm	LBS	PSI
11X4.00-5	4	TL	P508	3	1.5	100	270	325	46

13X5.00-6	2	TL	P508	3.5	3	120	311	295	20
13X5.00-6	4	TL	P508	3.5	3	120	322	440	40
13X6.50-6	4	TL	P508	5	3.5	160	333	460	28
15X6.00-6	2	TL	P508	4.5	4	155	363	365	14
15X6.00-6	4	TL	P508	4.5	4	160	380	570	30
15X6.00-6	6	TL	P508	4.5	4	160	385	710	40
15X6.00-6	10	TL	P508	4.5	4	160	385	1015	75
16X6.50-8	2	TL	P508	5.375	4	165	403	415	14
16X6.50-8	4	TL	P508	5.375	4	165	410	620	28
18x8.50-8	2	TL	P508	7	4.5	210	450	515	10
18x8.50-8	4	TL	P508	7	4.5	210	455	815	22
18x8.50-8	6	TL	P508	7	4.5	210	460	1050	34
18X9.50-8	2	TL	P508	7	3.8	223	455	695	12
18X9.50-8	4	TL	P508	7	3.8	223	460	1040	24
18X9.50-8	6	TL	P508	7	3.8	223	465	1320	36

## LAWN&GARDEN TIRE

### P5012



Size	PR	Tube Type	Tread Pattern	Rim Size	DEPTH (MM)	Section Width	Overall Diameter	Max Load	Inflation Pressure
						mm	mm	LBS	PSI
9X3.50-4	4	TL	P5012	2.75	3.5	88	228	352	50
16X6.50-8	2	TL	P5012	5.375	5.5	163	400	415	14
16X6.50-8	4	TL	P5012	5.375	5.5	163	400	620	28
16X6.50-8	6	TL	P5012	5.375	5.5	163	410	785	42
20X8.00-8	2	TL	P5012	6.5	5	210	488	600	10
20X8.00-8	4	TL	P5012	6.5	5	210	488	950	22

**Contact Us:**

cherry@debort.com

**DEBORT**

Devote ourselves to give you best Tyre and Rim solution.



**Cherry Quin** General Manager

**DEBORT CO., LIMITED**

Email: cherry@debort.com

Tel: 0086-532-80991938

Web: www.debort.com

Address: 2-3010, No.222 Shenzhen Road, Qingdao, China.

Cellphone : 0086-18660255278

Fax: 0086-532-80990998

Skype: cherryqueenchina

HIGH QUALITY

TIMELY DELIVERY

PERFECT SERVICE