



OUR FACTORY

Advanced Germany Technology and stick production control to make high quality products for you.



IMP-01

Low section implement tyres, offering high load capacity with minimum soil compaction.
Ideal tyres for modern farming, suitable for both on and off-the-road applications.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg) 40km/h	Inflation Pressure(kpa)
					Section Width	Overall Diameter		
7.00-12	6	IMP01	TT/TL	5.50*12	200	657	620	360
	12	IMP01	TT/TL	5.50*12	200	657	1800	860

10.5/65-16	10	IMP01	TT/TL	8*16	273	754	1550	380
	14	IMP01	TT/TL	8*16	273	754	1900	530
10.0/80-12	10	IMP01	TT/TL	7*12	264	710	1360	390
10.0/75-15.3	8	IMP01	TT/TL	9*15.3	264	760	1360	310
	10	IMP01	TT/TL	9*15.3	264	760	1550	390
	12	IMP01	TT/TL	9*15.3	264	760	1700	470
	18	IMP01	TT/TL	9*15.3	264	760	2360	710
11.5/80-15.3	10	IMP01	TT/TL	9*15.3	290	845	1950	340
	14	IMP01	TT/TL	9*15.3	290	845	2430	475
	16	IMP01	TT/TL	9*15.3	290	845	2575	510
	18	IMP01	TT/TL	9*15.3	290	845	2725	600
12.5/80-15.3	12	IMP01	TT/TL	9*15.3	307	889	2430	370
	14	IMP01	TT/TL	9*15.3	307	889	2650	430
	18	IMP01	TT/TL	9*15.3	307	889	3000	540
13.0/65-18	16	IMP01	TT/TL	11*18	335	889	2800	490
400/60-15.5	14	IMP01	TT/TL	13*15.5	403	868	2500	360
	16	IMP01	TT/TL	13*15.5	403	868	2900	400
10.5/80-18	10	IMP01	TL	9*18	273	885	2180	430
12.5/80-18	14	IMP01	TL	11*18	308	986	3000	430

IMP01



IMP04

Low section implement tyres, offering high load capacity with minimum soil compaction.
Ideal tyres for modern farming, suitable for both on and off-the-road applications.

IMP04

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter		
400/60-15.5	14	IMP04	TL	W13*15.5	404	868	2900	360
	16	IMP04	TL	W13*15.5	404	868	3250	400



IMP05

Low section implement tyres, offering high load capacity with minimum soil compaction.
Ideal tyres for modern farming, suitable for both on and off-the-road applications.

IMP05

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
15.0/55-17	14	IMP05	TL	W13*17	391	848	2575	360
	18	IMP05	TL	W13*17	391	848	3250	460
19.0/45-17	14	IMP05	TL	W16*17	490	863	2800	390
	18	IMP05	TL	W16*17	490	863	3250	340
500/50-17	14	IMP05	TL	W16*17	500	933	3250	360
	18	IMP05	TL	W16*17	500	933	4000	440



TRC02

Traction patterns, suitable designed for on and off-the-road use, in all weather conditions.
Patterns are engineered to provide excellent traction to drive wheels.
Suitable for both implement and industrial/construction applications.

TRC02

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
400/60-15.5	14	TRC02	TL	W13*15.5	404	868	2500	360
	16	TRC02	TL	W13*15.5	404	868	2900	400
500/50-17	14	TRC02	TL	W16X17	500	933	2246	360
	18	TRC02	TL	W16X17	500	933	3075	440



TRC03

Specially designed for high load capacities at low inflation pressures, minimizing soil compaction and preventing damage to crops.

Ideal suited for agricultural implement & trailer uses, both on and off-the-road.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
500/60-22.5	16	TRC03	TL	16*22.5	503	1191	4375	300
	18	TRC03	TL	16*22.5	503	1191	4875	320
550/60-22.5	16	TRC03	TL	16*22.5	537	1252	4875	280
600/50-22.5	16	TRC03	TL	20*22.5	592	1172	5150	260
600/55-22.5	16	TRC03	TL	20*22.5	592	1229	5000	200
650/50-22.5	16	TRC03	TL	20*22.5	645	1224	4500	200
700/40-22.5	16	TRC03	TL	24*22.5	699	1145	4500	170
700/50-22.5	16	TRC03	TL	24*22.5	699	1270	5600	180
710/40-22.5	16	TRC03	TL	24*22.5	711	1153	4500	170
600/55-26.5	16	TRC-03	TL	20*22.5	600	1330	6000	260
700/50-26.5	16	TRC-03	TL	24*22.5	700	1330	6700	220
800/45-26.5	16	TRC-03	TL	28*22.5	800	1330	7300	220

TRC03



TRC03N

Wider tyre for high load application at low inflation pressure.

Minimum soil compaction preventing damage to crops increasing the yield for longer time .

TRC03N has narrow overlap of cross bars at the centre compared to TRC03 for extra traction.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
355/55D625	14	G-2	TL	11.75x24.5	360	935		520
360/60-22.5	12	TRC03N	TL	11.75*22.5	364	1003	1750	160
385/65-22.5	18	G-2	TL	11.75*22.5	395	1072		830
400/55-22.5	16	TRC03N	TL	13*22.5	403	1011	3075	320
400/60-22.5	16	TRC03N	TL	13*22.5	403	1025	3075	320
445/65D22.5	18	G-2	TL	14x22.5	460	1160		830
500/45-22.5	16	TRC03N	TL	16*22.5	503	1021	3350	280
500/60-22.5	16	TRC03N	TL	16*22.5	503	1191	4375	300
	18	TRC03N	TL	16*22.5	503	1191	4875	320
550/45-22.5	16	TRC03N	TL	16*22.5	537	1066	4375	280
600/50-22.5	16	TRC03N	TL	20*22.5	591	1172	5150	260

TRC03N



300/65-12	8	TRC-03N	TL	10.00	290	670	1500	340
26x12-12	8	TRC-03N	TL	10.5I	300	660	1500	340

R1

Dual angled lugs ensure better traction and comfortable ride on the road. Suitable for general farming.

Also available in HD version with stronger casing and supperior tread compound for better life. Suitable for farming as well as for haulage purpose.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
10.0/80-12	10	R1	TL	7*12	264	708	1000	390
26*12.00-12	4	R1	TL	10.50L	307	648	810	140
31*15.5-15	8	R1	TL	13*15	391	792	1250	310
	12	R1	TL	13*15	391	792	1700	520
29x12.50-15	6	R1	TL	10.0*15	310	742	750	210
	8						975	310
31*15.5-15	8	R1	TL	13	391	792	1250	310
10.0/75-15.3	10	R1	TL	9*15.3	264	780	1090	300
	12	R1	TL	9*15.3	264	780	1180	400
11.5/80-15.3	10	R1	TL	9*15.3	290	867	1360	340
	14	R1	TL	9*15.3	290	867	1700	475
6.00-16	6	R1	TT	4.50E	165	745	495	250
7.50-16	6	R1	TT	5.50F	205	810	650	210
8.3-20	6	R1	TT	W7	210	895	695	240
405/70-20	14	R1	TL	13	407	1076	3250	350
8.3-24	6	R1	TT	W7	210	995	810	240
9.5-24	8	R1	TT	W8	240	1050	1110	280
11.2-24	8	R1	TT	W10	285	1105	1225	240
12.4-24	8	R1	TT	W11	315	1160	1415	230
14.9-24	10	R1	TT	W13	378	1265	1990	230
16.9-24	10	R1	TT	W15L	430	1335	2230	200
23.1-26	10	R1	TT	DW20	587	1605	3610	200
	12	R1	TT	DW20	587	1605	3900	200
11.2-28	8	R1	TT	W10	285	1205	1305	240
12.4-28	6	R1	TT	W11	315	1260	1275	170
	8	R1	TT				1510	230
13.6-28	8	R1	TT	W12	345	1310	1645	210
	10	R1	TT				1910	250
14.9-28	10	R1	TT	W13	378	1365	2120	230
16.9-28	10	R1	TT	W15L	430	1435	2380	200

R1



16.9-30	10	R1	TT	W15L	430	1485	2455	200
18.4-30	10	R1	TT	W16L	476	1550	2815	180
18.4-30	14	R1	TT	W16L	476	1550	3180	230
16.9-34	10	R1	TT	W15L	430	1585	2605	200
18.4-34	10	R1	TT	W16L	476	1655	2990	180
18.4-34	14	R1	TT	W16L	476	1655	3375	230
12-38	8	R1	TT	DW11	330	1575	1570	140
18.4-38	10	R1	TT	W16L	476	1755	3575	230
18.4-38	14	R1	TT	W16L	476	1755	3650	260
20.8-38	10	R1	TT	W18L	528	1835	4000	200

- R1W
- Dual angled Lugs to give better traction in the field and provide comfortable ride on road.
- Strong casing to carry heavy loads.
- More number of lugs provides uniform dustribution of load.
- Optimum tread depth and special tread compound for higher mileage.
- Most suitable for harvesting.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
24.5-32	14	R1W	TL	DW21	622	1803	4875	250
30.5L-32	18	R1W	TL	DW27	775	1820	6000	210
800/60-32	20	R1W	TL	DW27	790	1870	7750	320
900/60-32	20	R1W	TL	DW27	900	1900	8250	320
20.8-42	14	R1W	TL	W18	528	1935	7050	360

R1W



- R1 LS
- An excellent all-round tyre with DEBORT's most advanced technology concentrated in the foot print area.
- The 70 series tyre's traction capabilities are combined with surprisingly limited soil compactions, this is achieved by the design of the lugs, which retain their efficiency, thanks to regular wear characterisitics.

Size	TRA	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
				Section Width	Overall Diameter	40km/h	
380/70R24	R1 LS	TL	W12	380	1190	1900	240
420/70R24	R1 LS	TL	W13	418	1248	1900	160
480/70R34	R1 LS	TL	W15L	479	1580	2725	160
520/70R38	R1 LS	TL	W16L	516	1749	3350	160
620/70R42	R1 LS	TL	DW20B	610	1980	5300	240
520/85R42	R1 LS	TL	DW16L	516	1951	5150	240

R1 LS



R1 AW

Large contact area to provide best traction.

Best suitable for applications on wet and dry surfaces.

Application for lawn & garden, trencher equipment, aerial work platform and portable forklifts.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
26x12-12	8	R1-AW	TL	10.5I	300	660	1500	340
31x15.50-15	8	R1-AW	TL	13LB	380	800	2760	310

R1-AW



R1 Irrigation

Round shaped tyre reduces crop & soil damage.

Special tyre for irrigation application.

Tread pattern designed for sufficient traction and self cleaning property.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
14.9-24	6	R1 Irrigation	TT	W13	378	1265	1510	140
	8	R1 Irrigation	TT	W13			1760	180

R1-Irriation



PR-1

Specially designed for excellent traction & self cleaning property for wet soil & paddy fields.

Extra deep lugs provide improved performance with increased tyre life.

Natural rubber tread compound for better wear & tear resistance.

Tough nylon casing for longer tyre life.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
6.50-16	6	PR-1	TT	5.50F	165	830	565	250
13.6-38	10	PR-1	TT	W12	345	1710	2657	230
7.50-16	6	PR-1	TT	5.50F	195	890	750	300
8.3-20	8	PR-1	TT	W7	210	950	970	270
8.3-24	8	PR-1	TT	W7	210	1050	1135	270
11.2-24	8	PR-1	TT	W10	285	1205	1465	210
12.4-28	8	PR-1	TT	W11	315	1315	1785	200
11-32	10	PR-1	TT	W10	305	1460	1080	160
16.9-34	10	PR-1	TT	W15L	430	1670	2605	200

PR-1



R3

Tread specially designed to give minimum ground disturbance.

Flat and wide foot print makes suitable for use on soft soil, orchards and similar application.

Increased Tread depth and strong carcass ensures long life.

Suitable for road construction and other industrial tractors.

Available in HEAVY DUTY construction for severe application.

R3



R4

Drive Wheel tires for Industrial Tractors made with a pattern having extra wide lugs with extensive overlap at the centre, gives resistance to buckling, tearing and cracking.

Super compound and tough nylon casing gives best results on industrial use as well as for off-the-road and construction sites.

R4



Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
23.1-26	12	R3	TT/TL	DW20	587	1560	4750	162

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
27*8.5-15	8	R4	TL	7JA	215	655	850	350
27*10.5-15	10	R4	TL	8.5	259	670	1250	350
10.5/80-18	10	R4	TL	9*18	273	906	1360	370
10.5/80-18	12	R4	TL	W9	274	907	1550	420
12.5/80-18	12	R4	TL	9*18	308	986	1850	370
12.5/80-18	14	R4	TL	W9	308	987	2120	430
17.5L-24	10	R4	TL	W15L	445	1241	2800	220
19.5L-24	12	R4	TL	16*24	495	1314	3450	230
16.9-24	12	R4	TL	W15L	429	1309	3250	260
16.9-28	10	R4	TL	W15L	429	1410	3075	220
	12	R4	TL	W15L	429	1410	3450	260

F2

Three Rib front wheel tyres, designed for easy steering.
Strong nylon carcass ensures good performance on tractors fitted with implements such as a front loader or front mower.
Also suitable for use on certain agricultural machines.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
4.00-14	4	F2	TT	3.00D	110	590	270	340
4.00-14	6	F2	TT	3.00D	110	590	350	380
5.00-15	4	F2	TT	4J	140	665	365	280
5.00-15	6	F2	TT	4J	140	665	465	420
5.00-15	8	F2	TT	4J	140	665	500	470
5.50-16	6	F2	TT	4.00E	150	710	425	250
5.50-16	10	F2	TT	4.00E	150	710	525	370
6.00-16	8	F2	TT	4.50	153	715	615	470
6.50-20	4	F2	TT	5.00F	180	860	600	230
6.50-20	6	F2	TT	5.00F	180	860	725	310
6.50-20	8	F2	TT	5.00F	180	860	865	420
7.50-16	4	F2	TT	5.50F	205	810	605	200
7.50-16	6	F2	TT	5.50F	205	810	745	280
7.50-16	10	F2	TT	5.50F	205	810	870	370
9.00-16	10	F2	TT	6.00F	234	855	1250	390

F-2



F3

Low section height design, with highway tread pattern, suitable for agriculture implement & trailer, as also industrial applications such as Backhoe loader.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
11L-16	12	F-3	TL	8LB	279	838	1250	440
11L-16	8	F-3	TL	8LB	310	810	1130	220

F-3



I-1

Multi Rib, Low section I-1 tyres are designed to provide high flotation with minimum soil compaction with excellent load distribution.
On and off-the-road service.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	50km/h	
4.00-8	8	I-1	TT	3.00D	112	670	460	275
9.5L-15	8	I-1	TL	7.0*15	241	766	1120	300
	12	I-1	TL	7.0*15	241	766	1300	390
11L-15	8	I-1	TL	8.0*15	279	777	1150	250
	12	I-1	TL	8.0*15	279	777	1450	350
12.5L-15	8	I-1	TL	10.0*15	317	822	1360	250
	10	I-1	TL	10.0*15	317	822	1550	300
	12	I-1	TL	10.0*15	317	822	1750	360
14L-16.1	10	I-1	TL	11*16.1	355	985	1900	250
	14	I-1	TL	11*16.1	355	985	2360	360
16.5L-16.1	10	I-1	TL	14*16.1	419	1071	2360	250
	14	I-1	TL	14*16.1	419	1071	2900	330

I-1



FI

Multi Rib low section FI tyres offers high flotation.
Its strong nylon casing provides high load capacity and longer tyre life.
Specially designed for high speed applications on highway.

FI

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	100km/h	
11L-15	10	FI	TT/TL	8.0*15	279	777	1600	520
	12		TT/TL	8.0*15	279	777	1800	620
	14		TT/TL	8.0*15	279	777	2000	730
12.5L-15	8	FI	TT/TL	10.0*15	317	822	1700	410
	12		TT/TL	10.0*15	317	822	2500	730



F-101

Application to farm implement and wagons and trailers.

-Good guide performance, less rolling resistance.

-Good wear resistance, high floating force.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
18.0-15.5	14	F-101	TL	13	450	980	4185	350

F-101



MPT

Tyres for multi purpose trucks, designed for use on highways, off-the-road and agricultural applications.

Specially engineered tread pattern offers maximum flexibility.

-Good traction in all weather conditions.

-Good on-the-road driveability.

-Good self cleaning properties.

Size	PR	Tread Pattern	Tube Type	Rim Size	Inflated Dimensions(mm)		Max Load(kg)	Inflation Pressure(kpa)
					Section Width	Overall Diameter	40km/h	
16/70-20	14	MPT	TT	13.00	407	1076	3250	350

MPT



Contact Us:

cherry@debort.com

DEBORT

Devote ourselves to give you best Tyre and Rim solution.



Cherry Quin General Manager

DEBORT CO., LIMITED

Email: cherry@debort.com

Tel: 0086-532-80991938

Web: www.debort.com

Address: 2-3010, No.222 Shenzhen Road, Qingdao, China.

Cellphone : 0086-18660255278

Fax: 0086-532-80990998

Skype: cherryqueenchina

HIGH QUALITY

TIMELY DELIVERY

PERFECT SERVICE