

DEBORT

We DEBORT people devote ourselves to give you best Tyre and Rim solution.

OUR FACTORY

Advanced Germany Technology and stick production control to make high quality products for you.



TOUR RX1

Touring Performance



Optimized pitch design effectively reduces tire noise.
Anti-slip sipe improves driving stability and braking performance on wet road.
Streamline transversal grooves ensure safe handling and high speed stability.

SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section Width mm	Overall Diameter mm	MAX LOAD				Inflation Pressure		DEPTH (MM)
							SINGLE		DOUBLE		SINGLE		
							KG	LBS	KG	LBS	KPa	PSI	
145/70R12	69	T		4.50B	150	509	325	716	-	-	300	44	6.1
155/65R13	73	T		4.50B	157	532	365	805	-	-	300	44	7.3
155/70R13	75	T		4.50B	157	548	387	853	-	-	300	44	7.3
155/80R13	79	T		4.50B	157	578	437	963	-	-	300	44	7.3
155R12C	83/81	Q	6PR	4.50B	157	550	487	1075	462	1020	350	51	7.6
155R12C	88/86	Q	8PR	4.50B	157	550	487	1075	462	1020	350	51	7.6
165/65R13	77	T		5.00B	170	544	412	908	-	-	300	44	7.6
165/70R13	79	T		5.00B	170	562	437	963	-	-	300	44	7.6
165/70R14	81	T		5J	170	588	462	1019	-	-	300	44	7.6
165/80R13	83	T		4.50B	165	594	487	1074	-	-	300	44	7.8
175/60R13	77	T		5J	177	540	412	908	-	-	300	44	7.3
175/60R13	77	H		5J	177	540	412	908	-	-	300	44	7.3
175/65R14	82	T		5J	177	584	475	1047	-	-	300	44	7.8
175/65R14	82	H		5J	177	584	475	1047	-	-	300	44	7.8
175/65R14	86 XL	T		5J	177	584	530	1168	-	-	340	51	7.8
175/70R13	82	T		5.00B	177	576	475	1047	-	-	300	44	7.8
175/70R13	82	H		5.00B	177	576	475	1047	-	-	300	44	7.8
175/70R14	84	T		5J	177	602	500	1102	-	-	300	44	7.8
175/70R14	84	H		5J	177	602	500	1102	-	-	300	44	7.8
185/70R13	86	T		5.50B	189	590	530	1168	-	-	300	44	7.8
185/70R14	88	T		51/2J	189	616	560	1235	-	-	300	44	7.8
185/70R14	88	H		51/2J	189	616	560	1235	-	-	300	44	7.8

HT RX3

High performance



Four grooves with open shoulder provides perfect water evacuation.

Center rib design delivers better straight handling.

Improved shoulder sipes provide better handling during cornering and low noise emission.



SIZE	LOAD INDEX	SPEED RANGE	RIM SIZE	Section Width	Overall Diameter	MAX LOAD		Inflation Pressure		DEPTH (MM)	UTQG
				mm	mm	KG	LBS	KPa	PSI		
155/65R14	79 XL	T	4 1/2J	157	558	437	963	340	50	7.3	400 A A
165/65R14	79	T	5J	170	570	437	963	300	44	7.6	400 A A
175/65R13	80	T	5J	177	558	475	1047	300	44	7.8	400 A A
185/55R15	82	V	6J	194	585	475	1047	300	44	7.8	400 A A
185/60R14	82	H	5 1/2J	189	578	475	1047	300	44	7.8	400 A A
185/60R15	84	H	5 1/2J	189	603	500	1102	300	44	7.8	400 A A
185/65R14	86	T	5 1/2J	189	596	530	1168	300	44	7.8	400 A A
185/65R14	86	H	5 1/2J	189	596	530	1168	300	44	7.8	400 A A
185/65R15	88	T	5 1/2J	189	621	560	1235	300	44	7.8	400 A A
185/65R15	88	H	5 1/2J	189	621	560	1235	300	44	7.8	400 A A
195/50R15	82	H	6J	201	577	475	1047	300	44	7.8	400 A A
195/50R15	82	V	6J	201	577	475	1047	300	44	7.8	400 A A
195/55R15	85	V	6J	201	595	515	1135	300	44	7.8	400 A A
195/60R14	86	H	6J	201	590	530	1168	300	44	7.8	400 A A
195/60R15	88	H	6J	201	615	560	1235	300	44	7.8	400 A A
195/60R15	88	V	6J	201	615	560	1235	300	44	7.8	400 A A
195/65R15	91	H	6J	201	635	615	1356	300	44	7.8	400 A A
195/65R15	91	V	6J	201	635	615	1356	300	44	7.8	400 A A
195/70R14	91	T	6J	201	630	615	1356	300	44	7.8	400 A A
195/70R14	91	H	6J	201	630	615	1356	300	44	7.8	400 A A
205/55R16	91	H	6 1/2J	214	632	615	1356	300	44	7.8	400 A A
205/55R16	91	V	6 1/2J	214	632	615	1356	300	44	7.8	400 A A
205/60R15	91	H	6J	209	627	615	1356	300	44	7.8	400 A A
205/60R15	91	V	6J	209	627	615	1356	300	44	7.8	400 A A
205/60R16	92	H	6J	209	652	630	1389	300	44	7.8	400 A A
205/60R16	92	V	6J	209	652	630	1389	300	44	7.8	400 A A
205/60R16	96 XL	V	6J	209	652	710	1565	340	51	7.8	400 A A
205/65R15	94	H	6J	209	647	670	1477	300	44	7.8	400 A A
205/65R15	94	V	6J	209	647	670	1477	300	44	7.8	400 A A
205/70R14	98 XL	H	6J	209	644	750	1653	340	51	7.8	400 A A
205/70R14	98 XL	V	6J	209	644	750	1653	340	51	7.8	400 A A
215/60R16	95	H	6 1/2J	221	664	690	1521	300	44	7.8	400 A A
215/60R16	95	V	6 1/2J	221	664	690	1521	300	44	7.8	400 A A
215/60R16	99 XL	V	6 1/2J	221	664	775	1709	340	51	7.8	400 A A
215/65R16	102 XL	H	6 1/2J	221	686	850	1874	340	50	7.8	400 A A
215/65R16	102 XL	V	6 1/2J	221	686	850	1874	340	50	7.8	400 A A
215/65R16	98	H	6 1/2J	221	686	750	1653	300	44	7.8	400 A A
215/65R16	98	V	6 1/2J	221	686	750	1653	300	44	7.8	400 A A
P215/75R15	101	H	6J	216	703	825	1819	300	44	7.8	400 A A
P215/75R15	101	V	6J	216	703	825	1819	300	44	7.8	400 A A
225/60R16	98	H	6 1/2J	228	676	750	1653	300	44	7.8	400 A A
225/60R16	98	V	6 1/2J	228	676	750	1653	300	44	7.8	400 A A
P225/75R15	104	H	6J	223	719	900	1984	300	44	7.8	400 A A
P225/75R15	104	V	6J	223	719	900	1984	300	44	7.8	400 A A
P225/75R15	106 XL	H	6J	223	719	950	2094	340	50	7.8	400 A A
P225/75R15	106 XL	V	6J	223	719	950	2094	340	50	7.8	400 A A

SPORT RX6
Ultra High Performance



Special asymmetric pattern design provides excellent high speed and handling performance.

Spiral groove design contributes to outstanding water evacuation and wet grip.

Special compound design reduces heat generation and enhances grip performance under all road conditions.



SIZE	LOAD INDEX	SPEED RANGE	RIM SIZE	Section Width	Overall Diameter	MAX LOAD		Inflation Pressure		DEPTH (MM)	UTQG
				mm	mm	KG	LBS	KPa	PSI		
175/50R16	77	V	5 1/2J	182	582	412	908	300	44	7.8	340 A A
185/50R16	81	V	6J	194	592	462	1019	300	44	7.8	340 A A
195/40ZR17	81 XL	W	7J	200	588	462	1019	340	50	7.8	340 A A
195/45ZR16	84 XL	W	6 1/2J	195	582	500	1102	340	50	7.8	340 A A
195/45ZR17	85 XL	W	6 1/2J	195	608	515	1135	340	50	7.8	340 A A
195/50R16	88 XL	V	6J	201	602	560	1235	340	50	7.8	340 A A
195/55ZR16	87	W	6J	201	620	545	1201	300	44	7.8	340 A A
205/40R17	84 XL	W	7 1/2J	212	596	500	1102	340	50	7.8	340 A A
205/45ZR16	87XL	W	7J	206	590	545	1201	340	50	7.8	340 A A
205/45R17	88 XL	W	7J	206	616	560	1235	340	50	7.8	340 A A
205/50R16	87	W	6 1/2J	214	612	545	1201	300	44	7.8	340 A A
205/50R16	87	V	6 1/2J	214	612	545	1201	300	44	7.8	340 A A
205/50R17	93 XL	W	6 1/2J	214	638	650	1433	340	50	7.8	340 A A
205/55R16	91	W	6 1/2J	214	632	615	1356	300	44	7.8	340 A A
205/55R16	91	V	6 1/2J	214	632	615	1356	300	44	7.8	340 A A
205/55R16	94 XL	W	6 1/2J	214	632	670	1477	340	50	7.8	340 A A
205/55R16	94 XL	V	6 1/2J	214	632	670	1477	340	50	7.8	340 A A
215/35R18	84 XL	W	7 1/2J	218	607	500	1102	340	50	7.8	340 A A
215/40R17	87 XL	W	7 1/2J	218	604	545	1201	340	50	7.8	340 A A
215/40ZR18	85	W	7 1/2J	218	629	515	1135	300	44	7.8	340 A A
215/40ZR18	85	Y	7 1/2J	218	629	515	1135	300	44	7.8	340 A A
215/45R17	91 XL	W	7J	213	626	615	1356	340	50	7.8	340 A A
215/45R17	87	W	7J	213	626	545	1201	300	44	7.8	340 A A
215/45ZR18	89	Y	7J	213	651	580	1279	300	44	7.8	340 A A
215/45ZR18	89	W	7J	213	651	580	1279	300	44	7.8	340 A A
215/50ZR17	95 XL	W	7J	226	648	690	1521	340	50	7.8	340 A A
215/55R16	97 XL	W	7J	226	642	730	1609	340	50	7.8	340 A A
215/55R16	97 XL	V	7J	226	642	730	1609	340	50	7.8	340 A A
215/55ZR17	98 XL	W	7J	226	668	750	1653	340	50	7.8	340 A A
225/35ZR19	84	W	8J	230	641	500	1102	300	44	7.8	340 A A
225/35ZR20	90 XL	W	8J	230	666	600	1323	340	50	7.8	340 A A
225/40R18	92 XL	W	8J	230	637	630	1389	340	50	7.8	340 A A
225/45R17	94 XL	W	7 1/2J	225	634	670	1477	340	50	7.8	340 A A
225/45ZR18	95 XL	W	7 1/2J	225	659	690	1521	340	50	7.8	340 A A
225/50R16	96 XL	W	7J	233	632	710	1565	340	50	7.8	340 A A
225/50R16	96 XL	V	7J	233	632	710	1565	340	50	7.8	340 A A
225/50ZR17	94	W	7J	233	658	670	1477	300	44	7.8	340 A A
225/50ZR17	98 XL	W	7J	233	658	750	1653	340	50	7.8	340 A A
225/55R16	99 XL	W	7J	233	654	775	1709	340	50	7.8	340 A A
225/55R16	99 XL	V	7J	233	654	775	1709	340	50	7.8	340 A A
225/55R16	95	W	7J	233	654	690	1521	300	44	7.8	340 A A
225/55R16	95	V	7J	233	654	690	1521	300	44	7.8	340 A A
225/55R17	101 XL	W	7J	233	680	825	1819	340	50	7.8	340 A A
235/35ZR19	91 XL	Y	8 1/2J	241	647	615	1356	340	50	7.8	340 A A
235/40R18	95 XL	W	8 1/2J	241	645	690	1521	340	50	7.8	340 A A
235/45R17	97 XL	W	8J	236	644	730	1609	340	50	7.8	340 A A
235/45ZR18	98 XL	Y	8J	236	669	750	1653	340	50	7.8	340 A A
235/50ZR18	101 XL	Y	7 1/2	245	693	825	1819	340	50	7.8	340 A A
235/55R17	103 XL	W	7 1/2J	245	690	875	1929	340	50	7.8	340 A A
245/30ZR22	92 XL	W	8 1/2J	248	707	630	1389	340	50	7.8	340 A A
245/35ZR19	93 XL	W	8 1/2J	248	655	650	1433	340	50	7.8	340 A A
245/35ZR22	97 XL	W	8 1/2J	248	731	730	1609	340	50	7.8	340 A A
245/40ZR18	97 XL	W	8 1/2J	248	653	730	1609	340	50	7.8	340 A A
245/40ZR19	98 XL	W	8 1/2J	248	679	750	1653	340	50	7.8	340 A A
245/40ZR20	95	W	8 1/2J	248	704	690	1521	300	44	7.8	340 A A
245/45ZR17	99 XL	W	8J	243	652	775	1709	340	50	7.8	340 A A
245/45ZR18	100 XL	W	8J	243	677	800	1764	340	50	7.8	340 A A
245/45ZR19	102 XL	W	8J	243	703	850	1874	340	50	7.8	340 A A
245/45ZR20	99	W	8J	243	728	775	1709	300	44	7.8	340 A A
255/35ZR18	94 XL	W	9J	260	635	670	1477	340	50	7.8	340 A A
265/30ZR19	93 XL	W	9 1/2J	271	643	650	1433	340	50	7.8	340 A A
265/35ZR18	93	W	9 1/2J	271	643	650	1433	300	44	7.8	340 A A
275/30ZR20	93	W	9 1/2J	278	674	650	1433	300	44	7.8	340 A A
275/35ZR20	98	W	9 1/2J	278	700	750	1653	300	44	7.8	340 A A
275/40ZR19	105 XL	W	9 1/2J	278	703	925	2039	340	50	7.8	340 A A
275/40ZR20	106 XL	Y	9 1/2J	278	728	950	2094	340	50	7.8	340 A A
275/45ZR20	110 XL	Y	9J	273	756	1060	2337	340	50	7.8	340 A A
275/55R20	117 XL	V	8 1/2J	284	810	1285	2833	340	50	7.8	340 A A
285/45ZR22	114 XL	W	9 1/2J	285	815	1180	2601	340	50	7.8	340 A A
305/40ZR22	114 XL	W	11J	313	803	1180	2601	340	50	7.8	340 A A

MILEMAX RX501



SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section Width	Overall Diameter	MAX LOAD				Inflation Pressure		DEPTH (MM)
							SINGLE		DOUBLE		SINGLE		
					mm	mm	KG	LBS	KG	LBS	KPa	PSI	
155R13C	85/83	N	6PR	4.50B	157	578	515	1135	487	1074	350	51	8.0
155R13C	90/88	N	8PR	4.50B	157	578	600	1323	565	1245	450	65	8.0
165R13C	91/89	N	6PR	4 1/2J	165	594	615	1356	580	1269	375	54	8.0
165R13C	94/93	N	8PR	4 1/2J	165	594	670	1475	650	1435	450	65	8.0
165/70R13LT	88/86	T	6PR	5J	170	562	560	1235	530	1170	375	54	8.0
165/70R14LT	89/87	R	6PR	5J	170	588	580	1280	545	1200	375	54	8.0
175R13C	94/92	N	6PR	5.00B	177	610	670	1477	630	1389	375	54	8.0
175R13C	97/95	Q	8PR	5.00B	177	610	730	1609	690	1521	450	65	8.0

VAN RX5
Commercial Light Truck



Special compound design ensures a long mileage.
The combination of blocks provides a superior driving performance and a strong grip.
Three main grooves contribute to better water drainage and wet traction.



SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section	Overall	MAX LOAD				Inflation Pressure		DEPTH (MM)
					Width mm	Diameter mm	SINGLE		DOUBLE		SINGLE		
							KG	LBS	KG	LBS	KPa	PSI	
185R14C	102/100	Q	8PR	5 1/2J	188	650	850	1874	800	1764	450	65	8.4
185R14C	104	N	—	5 1/2J	188	650	850	1874	800	1764	450	65	8.4
185/75R16C	104/102	R	8PR	5J	184	684	900	1984.127	850	1873.9	475	68	8.4
195/65R16C	104/102	R	8PR	6J	201	660	900	1984	850	1874	475	68	9.7
195/65R16C	100/98	R	6PR	6J	201	660	800	1764	750	1653	375	54	9.7
195/70R15C	104/102	R	8PR	6J	201	655	900	1984	850	1874	450	65	10.2
195/75R16C	107/105	R	8PR	5 1/2J	196	698	975	2149	925	2039	475	68	8.7
195R14C	106/104	Q	8PR	5 1/2J	198	666	950	2094	900	1984	450	65	8.7
195R15C	106/104	Q	8PR	5 1/2J	198	690	950	2094	900	1984	450	65	8.7
205/65R16C	107/105	R	8PR	6J	209	672	975	2149	925	2039	475	68	9.7
205/70R15C	106/104	R	8PR	6J	209	669	950	2094	900	1984	450	65	10.2
215/65R16C	109/107	R	8PR	6 1/2J	221	686	1030	2271	975	2149	475	68	9.7
215/70R15C	109/107	S	8PR	6 1/2J	221	683	1030	2270	975	2150	450	65	9.7
215/70R16LT	104/102	N	8PR	6 1/2J	221	708	900	1984	850	1874	450	65	9.7
215/70R16LT	106/104	N	10PR	6 1/2J	221	708	950	2094	900	1984	550	80	9.7
215/70R16LT	100/97	N	6PR	6 1/2J	221	708	800	1765	730	1610	350	50	9.7
215/75R15LT	100/97	N	6PR	6J	216	703	800	1765	730	1610	350	50	9.7
215/75R16C	116/114	R	10PR	6J	216	728	1250	2756	1180	2601	525	76	9.7
215/75R16C	113/111	R	8PR	6J	216	728	1150	2535	1090	2403	475	68	9.7
225/65R16C	112/110	R	8PR	6 1/2J	228	698	1120	2469	1060	2337	475	68	9.7
225/70R15C	112/110	R	8PR	6 1/2J	228	697	1120	2469	1060	2337	450	65	10.2
235/65R16C	115/113	R	8PR	7J	240	712	1215	2679	1150	2535	475	68	9.7

SUV RX706
Suv/light truck



Wide-angle lateral grooves ensure excellent on-and-off road performance. Unique pattern design reduces noise generation,imporoves driving stability and wet grip performance. Optimized tread compound contributes to good durability,good driving comfort,high traction on both dry and wet grounds.

SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section	Overall	MAX LOAD				Inflation Pressure		DEPTH (MM)
					Width	Diameter	SINGLE		DOUBLE		SINGLE		
							mm	mm	KG	LBS	KG	LBS	
31x10.50R15LT	109	S	6PR	8 1/2J	268	775	1030	2270	-	-	350	50	10.5
LT225/75R16	115/112	S	10PR	6J	223	744	1215	2680	1120	2470	550	80	10.5
P235/65R17	103	T	-	7J	240	738	875	1929	-	-	300	44	8.2
235/65R17	104	T	-	7J	240	738	900	1984	-	-	300	44	8.2
P235/70R16	104	T	-	7J	240	736	900	1984	-	-	300	44	8.2
235/70R16	106	T	-	7J	240	736	950	2094	-	-	300	44	8.2
P235/75R15	108 XL	T	-	6 1/2J	235	733	990	2183	-	-	340	50	8.2
235/75R15	109XL	T	-	6 1/2J	235	733	1030	2271	-	-	340	50	8.2
LT235/85R16	120/116	S	10PR	6 1/2J	235	806	1380	3042	1260	2778	550	80	10.5
LT245/75R16	120/116	S	10PR	7J	248	774	1380	3042	1260	2778	550	80	10.5
LT265/70R17	121/118	S	10PR	8J	272	804	1450	3195	1320	2910	550	80	10.5
LT265/75R16	123/120	S	10PR	7 1/2	267	804	1550	3415	1400	3085	550	80	10.5
LT285/75R16	122/119	S	8PR	8J	286	834	1500	3305	1360	3000	450	65	10.5
LT305/70R16	118/115	S	8PR	9J	311	834	1320	2910	1215	2680	350	50	10.5
LT315/70R17	121/118	S	8PR	9 1/2J	323	874	1450	3195	1320	2910	350	50	10.5

SUV RX702
Suv/light truck



Optimized tread formula ensures excellent skid resistance on wet roads,and low rolling resistance on dry roads. Streamline transversal grooves ensure good wet traction and superior water evacuation. The designed pattern blocks ensure the driving power on various road surfaces.

SIZE	LOAD INDEX	SPEED RANGE	RIM SIZE	Section Width	Overall Diameter	MAX LOAD		Inflation Pressure		DEPTH (MM)	UTQG
				mm	mm	KG	LBS	KPa	PSI		
205/70R15	96	H	6J	209	669	710	1565	300	44	7.8	400 A A
215/65R16	98	H	6 1/2J	221	686	750	1653	300	44	7.8	400 A A
225/60R17	99	V	6 1/2J	228	702	775	1709	300	44	7.8	400 A A
225/65R17	102	V	6 1/2J	228	724	850	1874	300	44	7.8	400 A A
235/55R17	99	H	7 1/2J	245	690	775	1709	300	44	7.8	400 A A
235/55ZR18	104 XL	W	7 1/2J	245	715	900	1984	340	50	7.8	400 A A
235/60R16	100	H	7J	240	688	800	1764	300	44	7.8	400 A A
235/60R18	107 XL	V	7J	240	739	975	2149	340	50	7.8	400 A A
235/65R17	104	V	7J	240	738	900	1984	300	44	7.8	400 A A
245/35ZR20	95 XL	W	8 1/2J	248	680	690	1521	340	50	7.8	400 A A
245/35ZR20	95 XL	Y	8 1/2J	248	680	690	1521	340	50	7.8	400 A A
245/55ZR19	103	W	7 1/2J	253	753	875	1929	300	44	7.8	400 A A
245/65R17	107	H	7J	248	750	975	2149	300	44	7.8	400 A A
245/70R16	107	H	7J	248	750	975	2149	300	44	7.8	400 A A
255/35ZR20	97 XL	W	9J	260	686	730	1609	340	50	7.8	400 A A
255/35ZR20	97 XL	Y	9J	260	686	730	1609	340	50	7.8	400 A A
255/50ZR19	107 XL	W	8J	265	739	975	2149	340	50	7.8	400 A A
255/50ZR19	107 XL	Y	8J	265	739	975	2149	340	50	7.8	400 A A
255/55ZR18	109 XL	W	8J	265	737	1030	2271	340	50	7.8	400 A A
255/55ZR19	111 XL	W	8J	265	763	1090	2403	340	50	7.8	400 A A
255/60R18	112 XL	V	7 1/2J	260	763	1120	2469	340	50	7.8	400 A A
255/70R15	108	H	7 1/2J	260	739	1000	2205	300	44	7.8	400 A A
265/65R17	112	H	8J	272	776	1120	2469	300	44	7.8	400 A A
265/70R16	112	H	8J	272	778	1120	2469	300	44	7.8	400 A A
275/55R17	109	V	8 1/2J	284	734	1030	2271	300	44	7.8	400 A A
275/65R17	115	H	8J	279	790	1215	2679	300	44	7.8	400 A A
275/70R16	114	H	8J	279	792	1180	2601	300	44	7.8	400 A A
285/65R17	116	H	8 1/2J	292	802	1250	2756	300	44	7.8	400 A A

WINTER RX808

Winter Tire



Two wide main grooves and wide tread design ensures a superior handling performance on ice and snow ground. Sawtooth-shaped design on the tread guarantees excellent braking performance on ice and snow. Advanced silica compound offers enhanced traction and balance in winter driving conditions. Directional,v-shaped tread pattern improves water evacuation and enhances winter traction.

SIZE	LOAD INDEX	SPEED RANGE	RIM SIZE	Section Width	Overall Diameter	MAX LOAD		Inflation Pressure		DEPTH (MM)
				mm	mm	KG	LBS	KPa	PSI	
16S/70R13	79	T	5.00B	170	562	437	963	300	44	8.0
17S/65R14	82	T	5J	177	584	475	1047	300	44	8.1
17S/65R14	86 XL	T	5J	177	584	530	1168	340	50	8.1
17S/70R13	82	T	5.00B	177	576	475	1047	300	44	8.1
18S/60R14	82	T	5 1/2J	189	578	475	1047	300	44	8.2
18S/65R14	90 XL	T	5 1/2J	189	596	600	1323	340	50	8.2
18S/65R15	88	T	5 1/2J	189	621	560	1235	300	44	8.2
18S/70R14	88	T	5 1/2J	189	616	560	1235	300	44	8.2
19S/55R15	85	T	6J	201	595	515	1135	300	44	8.3
19S/60R15	88	T	6J	201	615	560	1235	300	44	8.3
19S/65R15	91	T	6J	201	635	615	1356	300	44	8.3
20S/55R16	91	T	6 1/2J	214	632	615	1356	300	44	8.4
20S/55R16	94 XL	T	6 1/2J	214	632	670	1477	340	50	8.4
20S/55R16	94 XL	H	6 1/2J	214	632	670	1477	340	50	8.4
20S/55R16	91	H	6 1/2J	214	632	615	1356	300	44	8.4
20S/65R15	94	T	6J	209	647	670	1477	300	44	8.4
20S/70R15	96	T	6J	209	669	710	1565	300	44	8.4
21S/55R16	93	T	7J	226	642	650	1433	300	44	8.5
21S/55R16	97 XL	T	7J	226	642	730	1609	340	50	8.5
21S/55R16	93	H	7J	226	642	650	1433	300	44	8.5
21S/55R16	97 XL	V	7J	226	642	730	1609	340	50	8.5
21S/55R17	94	T	7J	226	668	670	1477	300	44	8.5
21S/55R17	98 XL	V	7J	226	668	750	1653	340	50	8.5
21S/60R16	95	T	6 1/2J	221	664	690	1521	300	44	8.5
21S/60R16	99 XL	T	6 1/2J	221	664	775	1709	340	50	8.5
21S/60R16	99 XL	H	6 1/2J	221	664	775	1709	340	50	8.5
21S/60R16	95	H	6 1/2J	221	664	690	1521	300	44	8.5
21S/60R17	96	T	6 1/2J	221	690	710	1565	300	44	8.5
21S/60R17	96	H	6 1/2J	221	690	710	1565	300	44	8.5
21S/65R16	98	T	6 1/2J	221	686	750	1653	300	44	8.5
21S/65R16	98	H	6 1/2J	221	686	750	1653	300	44	8.5
21S/70R15	98	T	6 1/2J	221	683	750	1653	300	44	8.5
21S/70R16	100	H	6 1/2J	221	708	800	1764	300	44	8.5
21S/70R16	100	T	6 1/2J	221	708	800	1764	300	44	8.5
21S/75R15	100	T	6J	216	703	800	1764	300	44	8.5
22S/40R18	88	T	8J	230	637	560	1235	300	44	8.6
22S/40R18	92 XL	V	8J	230	637	630	1389	340	50	8.6
22S/45R17	94 XL	V	7 1/2J	225	634	670	1477	340	50	8.6
22S/45R17	94 XL	T	7 1/2J	225	634	670	1477	340	50	8.6
22S/45R18	95 XL	T	7 1/2J	225	659	690	1521	340	50	8.6
22S/45R18	95 XL	V	7 1/2J	225	659	690	1521	340	50	8.6
22S/50R17	94	T	7J	233	658	670	1477	300	44	8.6
22S/50R17	98 XL	V	7J	233	658	750	1653	340	50	8.6
22S/55R17	97	T	7J	233	680	730	1609	300	44	8.6
22S/55R17	101 XL	V	7J	233	680	825	1819	340	50	8.6
25S/55R18	105	T	8J	265	737	925	2039	300	44	8.9
22S/60R16	102 XL	H	6 1/2J	228	676	850	1874	340	50	8.6
22S/60R16	102 XL	T	6 1/2J	228	676	850	1874	340	50	8.6
22S/60R17	99	T	6 1/2J	228	702	775	1709	300	44	8.6
22S/60R17	99	H	6 1/2J	228	702	775	1709	300	44	8.6
22S/65R17	102	T	6 1/2J	228	724	850	1874	300	44	8.6
22S/65R17	102	H	6 1/2J	228	724	850	1874	300	44	8.6
23S/40R18	95 XL	T	8 1/2J	241	645	690	1521	340	50	8.7
23S/40R18	95 XL	V	8 1/2J	241	645	690	1521	340	50	8.7
23S/45R18	98 XL	V	8J	236	669	750	1653	340	50	8.7
23S/45R18	94	T	8J	236	669	670	1477	300	44	8.7
23S/55R17	103 XL	V	7 1/2J	245	690	875	1929	340	50	8.7
23S/55R17	99	T	7 1/2J	245	690	775	1709	300	44	8.7
23S/60R18	107 XL	V	7J	240	739	975	2149	340	50	8.7
23S/60R18	103	T	7J	240	739	875	1929	300	44	8.7
23S/65R17	108 XL	V	7J	240	738	1000	2205	340	50	8.7
23S/65R17	104	T	7J	240	738	900	1984	300	44	8.7
23S/70R16	109 XL	H	7J	240	736	1030	2271	340	50	8.7
23S/70R16	109 XL	T	7J	240	736	1030	2271	340	50	8.7
25S/55R18	109 XL	V	8J	265	737	1030	2271	340	50	8.9
25S/55R18	109XL	H	8J	265	737	1030	2271	340	50	8.9
25S/65R16	109	T	7 1/2J	260	738	1030	2271	300	44	8.9
25S/65R16	109	H	7J	260	738	1030	2271	300	44	8.9

WINTER RX818

Winter Tire



Serrated design in the outside main groove assures high grip and braking force on ICE&SNOW covered surfaces.
Deep and densely distributed grooves and steel sheet helps soften the tread, contributes to shorten braking distance on ice covered surface.

SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section Width	Overall Diameter	MAX LOAD				Inflation Pressure		DEPTH (MM)
							SINGLE		DOUBLE		SINGLE		
					mm	mm	KG	LBS	KG	LBS	KPa	PSI	
175/65R14	82	T	-	5J	177	584	475	1047	-	-	300	44	9.9
175/70R13	82	T	-	5J	177	576	475	1047	-	-	300	44	9.9
185/65R14	90 XL	T	-	5 1/2J	189	596	600	1323	-	-	340	50	9.9
185/65R15	88	T	-	5 1/2J	189	621	560	1235	-	-	300	44	9.9
195/60R15	88	T	-	6J	201	615	560	1235	-	-	300	44	9.9
195/65R15	91	T	-	6J	201	635	615	1356	-	-	300	44	9.9
205/55R16	91	T	-	6 1/2J	214	632	615	1356	-	-	300	44	9.9
205/55R16	94 XL	T	-	7J	214	632	670	1477	-	-	340	50	9.9
205/60R16	92	T	-	6J	209	652	630	1389	-	-	300	44	9.9
205/65R15	94	T	-	6J	209	647	670	1477	-	-	300	44	9.9
205/70R15	96	T	-	6J	209	669	710	1565	-	-	300	44	9.9
215/60R16	95	T	-	6 1/2J	221	664	690	1521	-	-	300	44	9.9
215/65R16	98	T	-	6 1/2J	221	686	750	1653	-	-	300	44	9.9
215/70R15	98	T	-	6 1/2J	221	683	750	1653	-	-	300	44	9.9
215/70R16	100	T	-	6 1/2J	221	708	800	1764	-	-	300	44	10.7
225/60R16	102 XL	T	-	6 1/2J	228	676	850	1874	-	-	340	50	9.9
225/65R17	102	T	-	6 1/2J	228	724	850	1874	-	-	300	44	10.7
235/65R17	104	T	-	7J	240	738	900	1984	-	-	300	44	10.7
235/70R16	109 XL	T	-	7J	240	736	1030	2271	-	-	340	50	10.7
245/45R17	95	T	-	8J	243	652	690	1521	-	-	300	44	9.9
LT245/75R16	120/116	Q	10PR	7J	248	774	1380	3040	1260	2780	550	80	13.1
265/70R17	115	T	-	8J	272	804	1215	2679	-	-	300	44	10.7
LT265/70R17	121/118	Q	10PR	8J	272	804	1450	3195	1320	2910	550	80	13.1

KARRIER RX566

Commercial Light Truck



Suitable for various light-load goods vehicles.
Excellent traction, braking and steering performance combined with good water dispersion and self-cleaning ability.

SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section Width	Overall Diameter	MAX LOAD				Inflation Pressure		DEPTH (MM)
							SINGLE		DOUBLE		SINGLE		
					mm	mm	KG	LBS	KG	LBS	KPa	PSI	
6.00R13LT	93/89	P	8PR	4.50B	164	650	650	1435	580	1280	415	60	8.2
6.00R14LT	95/90	P	8PR	4 1/2J	158	626	690	1521	600	1325	415	60	8.2
6.00R15LT	97/92	P	8PR	4.50E	170	705	730	1610	630	1390	415	60	8.2
6.50R16LT	107/102	M	10PR	5.50F	185	750	975	2150	850	1875	560	81	9.7
6.50R16LT	107/102	M	10PR	5.50F	185	750	975	2150	850	1875	560	81	9.7
7.00R16LT	109/107	M	8PR	5.50F	198	778	1025	2260	980	2160	450	65	10.7
7.00R16LT	113/111	M	10PR	5.50F	198	778	1130	2490	1075	2370	525	76	10.7
7.00R16LT	113/111	M	10PR	5.50F	198	778	1130	2490	1075	2370	525	76	10.7
7.00R16LT	107/102	M	8PR	5.50F	198	778	975	2150	850	1875	460	67	10.7
7.00R16LT	111/107	M	10PR	5.50F	198	778	1090	2405	975	2150	560	81	10.7
7.50R16LT	121/119	M	12PR	6.00G	215	805	1440	3175	1370	3020	650	94	10.7
7.50R16LT	123/121	M	14PR	6.00G	215	805	1510	3330	1440	3175	700	102	10.7
7.50R16LT	120/116	M	12PR	6.00G	215	805	1400	3085	1250	2755	700	102	10.7
7.50R16LT	122/118	M	14PR	6.00G	215	805	1500	3305	1320	2910	770	112	10.7

ST100 Trailer Tire



Provide good water dispersion for superior wet traction and the reinforced carcass enhance high speed durability.
Super structure and special profile provide high load capacity.
Lateral sipes in the tread blocks provide all-season grip throughout the life of the tyres.

SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section Width mm	Overall Diameter mm	MAX LOAD				Inflation Pressure		DEPTH (MM)
							SINGLE		DOUBLE		SINGLE		
							KG	LBS	KG	LBS	KPa	PSI	
ST175/80R13	6PR	91/87	L	5J	177	610	615	1360	545	1200	350	51	7.1
ST205/75R14	6PR	100/96	L	5 1/2J	203	664	800	1760	710	1570	350	51	7.6
ST205/75R14	8PR	105/101	L	5 1/2J	203	664	925	2040	825	1820	450	65	7.6
ST205/75R15	8PR	107/102	L	5 1/2J	203	689	975	2150	850	1870	450	65	7.6
ST205/75R15	6PR	101/97	L	5 1/2J	203	689	825	1820	730	1610	350	51	7.6
ST215/75R14	6PR	102/98	L	6J	216	678	850	1870	750	1650	350	51	7.6
ST225/75R15	10PR	117/112	L	6J	223	719	1285	2830	1120	2470	550	80	7.6
ST225/75R15	8PR	113/108	L	6J	223	719	1150	2540	1000	2200	450	65	7.6
ST235/80R16	10PR	123/119	L	6 1/2J	235	782	1550	3420	1360	3000	550	80	7.8
ST235/80R16	12PR	126/122	L	6 1/2J	235	782	1700	3750	1500	3305	660	95	7.8

MT200 Mud Tire



Especially designed for unpaved tough roads.
Various shoulder blocks promote driving and handling performance on tough roads.
Perfect grip on tough surfaces such as mud and sand.

SIZE	LOAD INDEX	SPEED RANGE	PR	RIM SIZE	Section Width mm	Overall Diameter mm	MAX LOAD				Inflation Pressure		DEPTH (MM)
							SINGLE		DOUBLE		SINGLE		
							KG	LBS	KG	LBS	KPa	PSI	
31x10.50R15LT	109	Q	6PR	8 1/2J	268	775	1030	2270	-	-	350	50	14.6
33x12.50R15LT	108	Q	6PR	10J	318	826	1000	2205	-	-	250	35	14.6
35x12.50R17LT	119	Q	8PR	10J	318	877	1360	3000	-	-	350	50	14.6
35x12.50R20LT	121	Q	10PR	10J	318	877	1450	3195	-	-	450	65	14.6
35x12.50R18LT	123	Q	10PR	10J	318	877	1550	3415	-	-	450	65	14.6
LT235/75R16	117/114	Q	10PR	6 1/2J	235	758	1285	2835	1180	2600	550	80	14.6
LT235/85R16	120/116	N	10PR	6 1/2J	235	806	1380	3042	1260	2778	550	80	14.6
LT245/75R16	120/116	N	10PR	7J	248	774	1380	3042	1260	2778	550	80	14.6
LT265/70R17	121/118	Q	10PR	8J	272	804	1450	3195	1320	2910	550	80	14.6
LT265/75R16	123/120	N	10PR	7 1/2J	267	804	1550	3415	1400	3085	550	80	14.6
LT275/70R18	125/122	Q	10PR	8J	279	843	1650	3640	1500	3305	550	80	14.6
LT285/70R17	121/118	Q	8PR	8 1/2J	292	832	1450	3195	1320	2910	450	65	14.6
LT285/75R16	122/119	Q	8PR	8J	286	834	1500	3305	1360	3000	450	65	14.6

Contact Us:

cherry@debort.com

DEBORT

Devote ourselves to give you best Tyre and Rim solution.



Cherry Quin General Manager

DEBORT CO., LIMITED

Email: cherry@debort.com

Tel: 0086-532-80991938

Web: www.debort.com

Address: 2-3010, No 222 Shenzhen Road, Qingdao, China.

Cellphone : 0086-18660255278

Fax: 0086-532-80990998

Skype: cherryqueenchina

HIGH QUALITY | TIMELY DELIVERY | PERFECT SERVICE