


OUR FACTORY

Advanced Germany Technology and stick production control to make high quality products for you.



Radial OTR tire

B02N



Graders 平地机



Dozers 推土机



Loaders 装载机



Articulated dump trucks
铰链式自卸车



With wide and stabile tread,Exellent traction and adhesion.Designed to deliver exceptional operator comfort and for articulated trucks.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 17.5R25 | ★★ | 182A2/167B | L-3/E-3 | 28 | TL | 14.00—1.5 |
| 20.5R25 | ★★ | 193A2/177B | L-3/E-3 | 31 | TL | 17.00—2.0 |
| 23.5R25 | ★★ | 201A2/185B | L-3/E-3 | 34 | TL | 19.00—2.5 |
| 26.5R25 | ★★ | 209A2/193B | L-3/E-3 | 27 | TL | 22.00—3.0 |
| 17.5R25 | ★★ | 182A2 | L-3 | 28 | TL | 14.00—1.5 |
| 20.5R25 | ★★ | 193A2 | L-3 | 28.5 | TL | 17.00—2.0 |
| 23.5R25 | ★★ | 201A2 | L-3 | 31.5 | TL | 19.00—2.5 |
| 26.5R25 | ★★ | 209A2 | L-3 | 34.5 | TL | 22.00—3.0 |
| 23.5R25 | ★★ | 201A2 | L-3 | 32 | TL | 19.50—2.5 |

B04S



Rigid dumpers 刚性自卸车



Bottom dumpers 底部自卸车



Reduced wheel spin in bad conditions;Good traction;Special abrasion resistance; Excellent resistance to damage;Suitable for dump loaders.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 18.00R33 | ★★ | 191B | E-4T | 54 | TL | 13.00—2.5 |
| 21.00R35 | ★★ | 201B | E-4T | 61 | TL | 15.00—3.0 |
| 24.00R35 | ★★ | 209B | E-4T | 68 | TL | 17.00—3.5 |


B07S



The rugged radial tire designed for forklift trucks, terminal tractors and other industrial equipments used in heavy-duty applications.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 18.00R25 | ★★★ | 214A5 | IND-4 | 63 | TL | 13.00-2.5 |

B01N



Excellent traction and stability. Deliver exceptional operator comfort. Designed for loaders, earthmovers and the equipment used in construction stockpile and truck-loading applications.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 17.5R25 | ★★ | 182A2/167B | L-3/E-3 | 28 | TL | 14.00—1.5 |
| 20.5R25 | ★★ | 193A2/177B | L-3/E-3 | 31 | TL | 17.00—2.0 |
| 23.5R25 | ★★ | 201A2/185B | L-3/E-3 | 34 | TL | 19.00—2.5 |
| 26.5R25 | ★★ | 209A2/193B | L-3/E-3 | 27 | TL | 22.00—3.0 |
| 17.5R25 | ★★ | 182A2 | L-3 | 28 | TL | 14.00—1.5 |
| 20.5R25 | ★★ | 193A2 | L-3 | 28.5 | TL | 17.00—2.0 |

| | | | | | | |
|---------|----|-------|-----|------|----|-----------|
| 23.5R25 | ★★ | 201A2 | L-3 | 31.5 | TL | 19.00—2.5 |
| 26.5R25 | ★★ | 209A2 | L-3 | 34.5 | TL | 22.00—3.0 |
| 23.5R25 | ★★ | 201A2 | L-3 | 32 | TL | 19.50—2.5 |

BXDN




Graders 平地机



Dozers 推土机



Loaders 装载机




Articulated dump trucks
铰链式自卸车



Special tread depth;Good traction in wet and muddy road;Special tread design guaranteed the integral beauty;Suitable for earthmovers and loaders.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 17. 5R25 | ★★ | 182A2/167B | L-3/E-3 | 28 | TL | 14.00-1.5 |
| 20.5R25 | ★★ | 193A2/177B | L-3/E-3 | 31 | TL | 17.00-2.0 |
| 23.5R25 | ★★ | 201A2/185B | L-3/E-3 | 42.5 | TL | 19.50-2.5 |
| 26.5R25 | ★★ | 209A2/193B | L-3/E-3 | 45 | TL | 22.00-3.0 |
| 29.5R25 | ★★ | 216A2/200B | L-3/E-3 | 48 | TL | 25.00-3.5 |

B02S



With wide and stabile tread,Exellent traction and adhesion.Designed to deliver exceptional operator comfort and for articulated trucks.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|------------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 600/65R25 | ★★ | 187A2/178B | L-3/E-3 | 35.5 | TL | 19.50—2.5 |
| 650/65R25 | ★★ | 193A2/180B | L-3/E-3 | 38.5 | TL | 19.50—2.5 |
| 750/65R25 | ★★ | 202A2/190B | L-3/E-3 | 44.5 | TL | 24.00—3.0 |
| 850/65R25 | ★★ | 196B/207A2 | L-3/E-3 | 48.5 | TL | 25.00—3.5 |
| 87565R29 | ★★ | 214A2/203B | L-3/E-3 | 52.5 | TL | 27.00—3.0 |
| 16.0065R25 | ★★ | 177B | E-4 | 46 | TL | 11.25—2.0 |

B03S



Excellent resistance to damage;Long tyre life;Good ground grasping and traction in harsh condition;Suitable for dump trucks.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 14.00R24 | ★★★ | 168B | E-4 | 38 | TT | 10 |
| 14.00R25 | ★★★ | 168B | E-4 | 38 | TL | 10.0-1.5 |
| 18.00R25 | ★★ | 185B | E-4 | 47 | TL | 13.00-2.5 |

B05N



Cranes 起重机



Fire&Rescue 救护车



transport 运输卡车




Flatbed 平板车



High-speed capability;Exceptional operate comfort;Intermediate transverse block pattern;Long tyre life;Good traction;Suitable for cranes.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|----------------------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 14.00R24(385/95R24) | ★★★ | 170E | E-2 | 23 | TT | 10.00W |
| 14.00R25(385/95R25) | ★★★ | 170E | E-2 | 23 | TL | 10.00—1.5 |
| 16.00R25(445/95R25) | ★★★ | 170F | E-2 | 28 | TL | 11.25—2.0 |
| 17.5R25(445/80R25) | ★★★ | 170E | E-2 | 28 | TL | 14.00—1.5 |
| 20.5R25(525/80R25) | ★★★ | 179E | E-2 | 31 | TL | 17.00—2.0 |
| 18.00R25(505/95R25) | ★★★ | 186E | E-2 | 28 | TL | 13.00—2.5 |

B06S



Pattern designed for trucks;Provide excellent protection at high speed;Long tyre life in harsh condition;Excellent resistance to damage;Suitable for many working conditions.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 18.00R25 | ★★ | 185B | E-4P | 47 | TL | 13.00-2.5 |
| 18.00R33 | ★★ | 191B | E-4P | 49 | TL | 13.00-2.5 |
| 21.00R33 | ★★ | 200B | E-4P | 54 | TL | 15.00-3.0 |

BDRS



Excellent traction capabilities;Long tyre life;Available with either cut-resistance or high-speed capability;High protection in harsh conditions;Designed for trucks.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 18.00R33 | ★★ | 191B | E-4R | 54 | TL | 13.00-2.5 |
| 21.00R35 | ★★ | 201B | E-4R | 54 | TL | 15.00-3.0 |
| 24.00R35 | ★★ | 209B | E-4R | 58 | TL | 17.00-3.5 |


BDTS



Good traction,operate comfort;Heat resistance for high speed and cut resistance;Good penetrate resistance; Suitable for many working conditions.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 23.5R25 | ★★ | 185B | E-4 | 48 | TL | 19.50-2.5 |
| 26.5R25 | ★★ | 193B | E-4 | 52 | TL | 22.00-3.0 |
| 29.5R25 | ★★ | 200B | E-4 | 57 | TL | 25.00-3.5 |
| 29.5R29 | ★★ | 202B | E-4 | 57 | TL | 25.00-3.5 |

BGZN



High-speed capability;Closed shoulder design;Variable pitch to minimize the noise;Special abrasion resistance.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|---------------------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 14.00R24(385/95R24) | ★★ | 170E | E-2 | 23 | TT | 10.00W |
| 14.00R25(385/95R25) | ★★ | 170E | E-2 | 23 | TL | 10.00—1.5 |
| 16.00R25(445/95R25) | ★★ | 174F | E-2 | 28 | TL | 11.25—2.0 |

BLGN



| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|------------|----------|-------------|------|-------------------|
| | | | | mm | | (RIMWIDTH&FLANGE) |
| 16.00r24 | ★★ | 163 | L-2/G-2 | 27 | TL | 10 |

BWYN

Applications:



Loaders 装载机



Articulated dump trucks
铰链式自卸车



Cranes 平地机



Telescopic Handlers
自动伸缩臂装运机



Cranes 起重机



Special abrasion resistance and good traction;All season use;Designed for graders and cranes with special use on ice and snow.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|-------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH&FLANGE) |
| 16.00R25 | ★★★ | 174F | E-2 | 28 | TL | 14.00-1.5 |
| 20.5R25 | ★★ | 193A2/161B | L-2/E-2 | 31 | TL | 17.00-2.0 |
| 23.5R25 | ★★ | 201A2/170B | L-2/E-2 | 34 | TL | 19.50-2.5 |
| 26.5R25 | ★★ | 209A2/193B | L-2/E-2 | 37 | TL | 22.00-3.0 |
| 29.5R25 | ★★ | 216A2/200B | L-2/E-2 | 43.5 | TL | 25.00-3.5 |
| 15.5R25 | ★★ | 176A2/160B | L-2/E-2 | 25 | TL | 12.00-1.3 |
| 17.5R25 | ★★ | 182A2/167B | L-2/E-2 | 28 | TL | 14.00-1.5 |

LCHS



Loaders 装载机



Dozers 推土机



Cranes 平地机



Shuttle Trucks Underground
地下运输车



Good traction and protection; Stable,comfortable ride;Special abrasion resistance with long-lasting tread life;Suitable for many conditions such as stone pit industry zone and underground mine.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 12.00R24 | ★★★ | 178A5 | IND-4 | 41.5 | TL | 8.5 |
| 16.00R25 | ★★★ | 200A5 | IND-4 | 72.5 | TL | 11.25-2.0 |
| 18.00R33 | ★★★ | 219A5 | IND-4 | 73 | TL | 13.00-2.5 |
| 18.00R25 | | 214A5 | IND-4 | 63 | TL | 13.00-2.5 |

LCHS+



Loaders 装载机



Dozers 推土机



Cranes 平地机



Shuttle Trucks Underground
地下运输车



Good traction and protection; Stable,comfortable ride;Special abrasion resistance with long-lasting tread life;Suitable for many conditions such as stone pit industry zone and underground mine.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 17.5R25 | ★★ | 182A2 | L-5 | 65 | TL | 14.00-1.5 |
| 20.5R25 | ★★ | 193A2 | L-5 | 72 | TL | 17.00-2.0 |
| 23.5R25 | ★★ | 201A2 | L-5 | 83 | TL | 19.50-2.5 |

| | | | | | | |
|----------|----|-------|-----|-----|----|-----------|
| 26.5R25 | ★★ | 209A2 | L-5 | 90 | TL | 22.00-3.0 |
| 29.5R25 | ★★ | 216A2 | L-5 | 100 | TL | 25.00-3.5 |
| 29.5R29 | ★★ | 218A2 | L-5 | 100 | TL | 25.00-3.5 |
| 18.00R25 | ★★ | 204A2 | L-5 | 80 | TL | 13.00-2.5 |
| 35/65R33 | ★★ | 224A2 | L-5 | 97 | TL | 28.00-3.5 |

LOFN



| Tire Size | Star Rating | Max speed | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|-----------|----------|-------------|-------|----------------------|
| | | | | mm | | (RIMWIDTH&FLANGE) |
| 13.00R25 | ★★★ | 50 | E-3 | 28 | TT/TL | 8.5 |
| 14.00R24 | ★★★ | 50 | E-3 | 28 | TL | 10 |
| 14.00R25 | ★★★ | 50 | E-3 | 28 | TT/TL | 10.0/2.0 10.0/1.5 |

M08S



The rugged radial tire designed for forklift trucks,terminal tractors and other industrial equipments used in heavy-duty applications.

| Tire Size | Star Rating | Load Index | Pattern No. | TRA Code | Standard Rim | Inflated Tire Size (mm) | | Max load(kg) | Standard pressure(bar) | Max speed(km/h) | tube / tubeless | Tread Depth (mm) |
|-----------|-------------|------------|-------------|----------|--------------|--------------------------|---------------|--------------|------------------------|-----------------|-----------------|--------------------|
| | | | | | | SECTION WIDTH±1.5% | DIAMETER±3.5% | | | | | |
| 16.00R25 | ☆☆☆ | 200A5 | M08S | IND4 | 11.25/2.0 | 1522 | 432 | 14000 | 10.00 | 25 | TL | 72.5 |
| 18.00R25 | ☆☆☆ | 214A5 | M08S | IND4 | 13.00/2.5 | 1673 | 498 | 17500 | 10.00 | 25 | | 63 |
| 18.00R33 | ☆☆☆ | 219A5 | M08S | IND4 | 13.00/2.5 | 1877 | 498 | 21200 | 10.00 | 25 | | 73 |

MWS



Excellent traction capabilities;Long tyre life;Available with either cut-resistance or high-speed capability;High protection in harsh conditions;Designed for trucks.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 23.5R25 | ★★ | 201A2 | L-4 | 51 | TL | 19.50-2.5 |
| 26.5R25 | ★★ | 209A2 | L-4 | 60 | TL | |

SMS+



Smooth tread pattern;Special cut resistance and loading capabilities ; Reliable in the most extreme harsh conditions;Suitable for stone pit ,industry zone and underground mine.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | tube / tubeless | Standard Rim | Inflated Tire Size (mm) | | Max load(kg) | Standard pressure(bar) | Max speed(km/h) |
|-----------|-------------|------------|----------|-------------|-----------------|--------------|--------------------------|----------------|--------------|------------------------|-----------------|
| | | | | | | | SECTION WIDTH±1.5% | DIAME TER±3.5% | | | |
| 23.5R25 | ☆☆ | 201 | L5 | 78 | TL | 19.50/2.5 | 1673 | 597 | 14500 | 6.5 | 10 |
| 26.5R25 | ☆☆ | 209 | L5 | 87 | TL | 22.00/3.0 | 1798 | 673 | 18500 | 6.5 | 10 |
| 29.5R25 | ☆☆ | 216 | L5 | 95 | TL | 25.00/3.5 | 1921 | 750 | 22400 | 6.5 | 10 |
| 29.5R29 | ☆☆ | 218 | L5 | 95 | TL | 25.00/3.5 | 2023 | 750 | 23600 | 6.5 | 10 |

MWS+



Good traction and protection; Stable, comfortable ride; Special abrasion resistance with long-lasting tread life; Suitable for many conditions such as stone pit industry zone and underground mine.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 17.5R25 | ★★ | 182A2 | L-5 | 68 | TL | 14.00-1.5 |
| 20.5R25 | ★★ | 193A2 | L-5 | 78 | TL | 17.00-2.0 |
| 23.5R25 | ★★ | 201A2 | L-5 | 87 | TL | 19.50-2.5 |
| 26.5R25 | ★★ | 209A2 | L-5 | 96 | TL | 22.00-3.0 |
| 29.5R25 | ★★ | 216A2 | L-5 | 104 | TL | 25.00-3.5 |
| 29.5R29 | ★★ | 218A2 | L-5 | 104 | TL | 25.00-3.5 |
| 35/65R33 | ★★ | 224A2 | L-5 | 97 | TL | 28.00-3.5 |

Radial OTR Gianttire

HLG01



Rigid dumpers 刚性自卸车



Rock-deep tread with tough lug and sidewall protectors.Specially designed for large dump trucks engaged in earthmoving.High resistance to cutting ang chipping for long tread life.

| Tire Size | Star Rating | Load Index | TRA Code | Tread Depth | Type | Standard Rim |
|-----------|-------------|--------------|----------|-------------|------|--------------------|
| | | Speed Symbol | | mm | | (RIMWIDTH& FLANGE) |
| 27.00R49 | ★★ | 223B | E-4 | 68 | TL | 19.50-4.0 |
| 30.00R51 | ★★ | 230B | E-4 | 74 | TL | 22.00-4.5 |
| 33.00R51 | ★★ | 235B | E-4 | 80 | TL | 24.00-5.0 |
| 36.00R51 | ★★ | 241B | E-4 | 88 | TL | 26.00-5.0 |
| 37.00R57 | ★★ | 246B | E-4 | 89 | TL | 27.00-6.0 |
| 40.00R57 | ★★ | 250B | E-4 | 93 | TL | 29.00-6.0 |

Bias OTR tire

E3/L3



Wide pattern block design in their thread cap, good proterty of wear-resistance, shock-resistance, special design of shoulder pattern,each to expel mud, possesing property of self-clean and preventing sideslip,be suitable to work of loading, bulldozing under all kinds of complex conditions.



| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|----------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 29.5-25 | 28 | 36 | 25.00/3.6 | 1923 | 750 | 17500/11500 | 425/325 |
| | 32 | 36 | 25.00/3.6 | 1923 | 750 | 17900/12300 | 435/332 |
| 26.5-25 | 28 | 36 | 22.00/3.0 | 1750 | 675 | 15500/10000 | 475/350 |
| | 32 | 36 | 22.00/3.0 | 1750 | 675 | 16275/10500 | 498/367 |
| 23.5-25 | 20 | 32 | 19.50/2.5 | 1615 | 595 | 10900/7300 | 375/300 |
| | 24 | 32 | 19.50/2.5 | 1615 | 595 | 12500/8000 | 475/300 |
| 20.5-25 | 20 | 26 | 17.00/2.0 | 1490 | 520 | 8835/5580 | 420/304 |
| | 24 | 26 | 17.00/2.0 | 1490 | 520 | 9500/6000 | 450/325 |
| 18.00-25 | 28 | 26 | 13.00/2.5 | 1615 | 500 | 13600/8000 | 650/500 |
| | 32 | 26 | 13.00/2.5 | 1615 | 500 | 15000/8750 | 750/575 |
| 17.5-25 | 16 | 26 | 14.00/1.5 | 1350 | 445 | 7300/4250 | 475/300 |
| | 20 | 26 | 14.00/1.5 | 1350 | 445 | 8250/5000 | 575/400 |
| 16.00-25 | 28 | 26 | 11.25/2.0 | 1495 | 430 | 10600/6000 | 650/475 |
| 16.00-24 | 20 | 26 | 11.25/2.0 | 1490 | 430 | 9434/5340 | 550/400 |

| | | | | | | | |
|------------|----|----|-----------|------|-----|------------|---------|
| 10.00-24 | 24 | 26 | 11.25/2.0 | 1490 | 430 | 10600/6000 | 650/475 |
| 15.5-25 | 20 | 26 | 12.00/1.3 | 1275 | 395 | 6800/3850 | 460/285 |
| 14.00-24 | 16 | 28 | 10.00 | 1370 | 375 | 7565/4116 | 550/375 |
| | 20 | 28 | 10.00 | 1370 | 375 | 8500/4625 | 700/475 |
| 9.00-20 | 16 | 18 | 7.00 | 1038 | 259 | 2900/- | 880/- |
| 11.00-20 | 16 | 18 | 8.00 | 1105 | 293 | 3350/- | 810/- |
| 12.00-20 | 16 | 18 | 8.00 | 1145 | 315 | 3550/- | 740/- |
| 13.00-25 | 28 | 27 | 10.00 | 1300 | 350 | 4600 | 700 |
| 14.00-20 | 20 | 18 | 10.00 | 1265 | 375 | 5225/- | 770/- |
| 10.00-16 | 16 | 18 | 6.50 | 910 | 275 | 2742 | 565 |
| 9.00-16 | 16 | 18 | 6.50 | 890 | 255 | 1955 | 630 |
| 8.25-16 | 16 | 18 | 6.50 | 855 | 235 | 1800 | 7300 |
| 7.50-16 | 16 | 18 | 6.00 | 761 | 185 | 1180 | 630 |
| 16/70-16 | 18 | 25 | 13.00 | 870 | 410 | 5150/2900 | 450/350 |
| 16/70-20 | 18 | 25 | 13.00 | 1075 | 410 | 5150/2900 | 450/350 |
| 16/70-24 | 18 | 25 | 13.00 | 1175 | 410 | 5650/4750 | 450/325 |
| 20.5/70-16 | 14 | 25 | 8.50 | 1075 | 410 | 350 | 2850 |

L-5S



Smooth thickening of the tread compound formula design,special, the cutting resistance, antipiercing,wear-resisting performance is better.Can be assembled in a tunnel, tunnel, mine and other rock site operation LHD, loaders and other engineering machinery vehicle.

| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|---------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 23.5-25 | 20 | 78 | 19.50/2.5 | 1650 | 595 | 10900/7300 | 375/300 |
| 26.5-25 | 28 | 36 | 22.00/3.0 | 1750 | 675 | 15500/10000 | 475/350 |
| | 32 | 36 | 22.00/3.0 | 1750 | 675 | 16275/10500 | 498/367 |

E3E



Wide pattern block design in their thread cap,good property of wear-resistance, shock-resistance,special design of shoulder pattern, each to expel mud,possesing proterty of self-clean and preventing sideslip,be suitable to work of loading, bulldozing under all kinds of complex conditions.



| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|---------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 26.5-25 | 28 | 36 | 22.00/3.0 | 1750 | 675 | 15500/10000 | 475/350 |
| | 32 | 36 | 22.00/3.0 | 1750 | 675 | 16275/10500 | 498/367 |
| 23.5-25 | 20 | 32 | 19.50/2.5 | 1615 | 595 | 10900/7300 | 375/300 |
| | 24 | 32 | 19.50/2.5 | 1615 | 595 | 12500/8000 | 475/300 |
| 20.5-25 | 20 | 26 | 17.00/2.0 | 1490 | 520 | 8835/5580 | 420/304 |
| | 24 | 26 | 17.00/2.0 | 1490 | 520 | 9500/6000 | 450/325 |
| 17.5-25 | 16 | 26 | 14.00/1.5 | 1350 | 445 | 7300/4250 | 475/300 |
| | 20 | 26 | 14.00/1.5 | 1350 | 445 | 8250/5000 | 575/400 |

E-4



This series of products through the optimization pattern, outline design and construction design based on GX168 pattern, based on ensuring the product performance and greatly improves the tire price, especially suitable for the road conditions are not harsh the use of vehicle speed, working environment better mining area.

Pattern design optimization, strengthen the pattern block rigid, ensure the tire has a bearing performance and durability of pavement superior, grip and good traction perfect.



| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|----------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 18.00-25 | 18 | 32 | 13.00-25 | 1615 | 495 | 11500/5600 | 475/325 |
| 18.00-25 | 32 | 32 | 13.00-25 | 1615 | 500 | 15000/8750 | 750/575 |
| 23.5-25 | 20 | 32 | 19.50/2.5 | 1615 | 595 | 10900/7300 | 375/300 |

This pattern is a heavy truck, truck tire's flagship product, the product takes full account of the characteristics of non-road tires, the outline design, the matrix strength is high, the sidewall protection performance is good, the tread of cutting resistance, can adapt to all kinds of Mines operating environment, especially to reflect more products of excellent performance in harsh working environment.



| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|-----------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 11.00-20 | 18 | 25 | 8.0 | 1105 | 293 | 3350 | 810 |
| | 20 | | | | | 3650 | 910 |
| 12.00-20 | 18 | 25.5 | 8.5 | 1145 | 315 | 3750 | 810 |
| | 20 | | | | | 4000 | 880 |
| 13.00- 25 | 28 | 27 | 10.0 | 1300 | 350 | 4600 | 700 |
| 14.00- 20 | 20 | 26 | 10.0 | 1265 | 375 | 5225 | 770 |
| | 24 | | | | | 5600 | 890 |
| 14.00- 24 | 24 | 26.5 | 10.0 | 1370 | 375 | 5150/9500 | 575/850 |
| | 28 | | | | | 5600/10000 | 650/925 |
| 14.00- 25 | 36 | 27 | 10.0 | 1370 | 375 | 5600 | 650 |
| 10.00- 20 | 16 | 25 | 14.00/1.5 | 1350 | 375 | 7300/4250 | 475/300 |
| | | | | | | 8250/5000 | 575/400 |

E-3



Grip strength, good self-cleaning capacity.Traction performance high, prick resistant,abrasion resistance Suitable for soft terrain,sand and gravel mines operating environment.

| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|----------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 13.00-25 | 28 | 27 | 10.0 | 1300 | 350 | 4600 | 700 |
| 14.00-24 | 16 | 28 | 10.00 | 1370 | 375 | 7565/4116 | 650/420 |
| | 20 | | | | | 8500/4625 | 700/475 |
| 14.00-25 | 36 | 27 | 10.0 | 1370 | 375 | 5600 | 650 |

GX977



Pattern design optimization, strengthen the pattern block rigid,ensure the tire has a bearing performance and durability of pavement superior,grip and good traction perfect.Especially be suitable for the road conditions are not harshmthe use of vehicle speed, working envir-onment better mining area.

| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|----------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 11.00-20 | 16 | 18 | 8.00 | 1105 | 293 | 3350/- | 810/- |
| 12.00-20 | 16 | 18 | 8.00 | 1145 | 315 | 3550/- | 740/- |

R-3



Flotage type, run stably, shoulder area is circular arc design, well-distributed pressure of connecting with ground. It possesses the good property of passing and reducing quake, suitable to single-cylinder road roller.

| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|---------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 23.1-26 | 12 | 16 | DW20 | 1500 | 595 | 3655 | 200 |

G2/L2



It is a tough road grader tire developed especially to withstand rugged terrains. Its massive lugs are reinforced and connected to an extra thick center tread rubber belt. This design feature enables the tire to be used for long lasting service in tough conditions. The nylon construction enables the tire to overcome obstacles and provides a longer wearing period.

| NO | PR | THEAD DEPTH | STANDAR D RIM | OVERALL DIA | SECTION WIDTH | MAX LOAD(KG) | MAX PRESSURE (KPA) |
|----------|----|-------------|------------------|-------------|------------------|-----------------|--------------------------|
| | | mm | | mm | mm | 10/50 (km/h) | 10/50 (km/h) |
| 23.5-25 | 16 | 28 | 19.50/2.5 | 1615 | 595 | 4750 | 200 |
| | 20 | 28 | 19.50/2.5 | 1615 | 595 | 5450 | 250 |
| 20.5-25 | 16 | 28 | 17.00/2.0 | 1490 | 520 | 4000 | 225 |
| | 20 | 28 | 17.00/2.0 | 1490 | 520 | 4500 | 275 |
| 17.5-25 | 16 | 26 | 14.00/1.5 | 1350 | 445 | 3350 | 275 |
| | 20 | 26 | 14.00/1.5 | 1350 | 445 | 3650 | 325 |
| 13.00-24 | 12 | 25 | 8 | 2725 | 300 | 6590/3080 | 460/320 |
| | 14 | 25 | 8 | 3000 | 350 | 7100/3650 | 490/350 |
| 14.00-24 | 16 | 25 | 10.00 | 1345 | 360 | 7300/3650 | 550/375 |
| | 18 | 25 | 10.00 | 1345 | 360 | 7800/3900 | 600/425 |

JZ688



Apply to all kinds of forklift trucks, with load, wear resistance and low rolling resistance function. For domestic and foreign forklift trucks special.

| NO | STANDARD RIM | OVERALL DIA mm | SECTION WIDTH mm | MAX LOAD(KG) | | | | | | OYTER |
|---------|--------------|----------------|------------------|--------------|-------|----------------|------------|----------------|------------|-------|
| | | | | Load | Drive | Steering steer | Load Drive | Steering steer | Load Drive | |
| 4.00-8 | 3.00 | 400 | 105 | 1055 | 845 | 1020 | 765 | 950 | 715 | 730 |
| 5.00-8 | 3.00 | 450 | 120 | 1210 | 970 | 1178 | 880 | 1095 | 820 | 840 |
| 18*7-8 | 4.33 | 440 | 150 | 2350 | 1880 | 2265 | 1700 | 2110 | 1585 | 1620 |
| 6.00-9 | 4.00 | 515 | 135 | 1920 | 1535 | 1855 | 1390 | 1730 | 1295 | 1325 |
| 6.00-15 | 4.50 | 710 | 148 | 2380 | 2095 | 2705 | 2000 | 2455 | 1820 | 1895 |
| 6.50-10 | 5.00 | 560 | 145 | 2640 | 2110 | 2545 | 1910 | 2370 | 1780 | 1820 |
| 6.50-16 | 5.50 | 748 | 165 | 3425 | 2740 | 3285 | 2465 | 3080 | 2310 | 2365 |
| 7.00-9 | 5.00 | 530 | 150 | 2790 | 2250 | 2675 | 2080 | 2560 | 1980 | 1940 |
| 7.00-12 | 5.00 | 683 | 168 | 3015 | 2410 | 2910 | 2185 | 2710 | 2035 | 2075 |
| 7.00-15 | 5.50/6.00 | 759 | 177 | 3590 | 2870 | 3465 | 2600 | 3225 | 2420 | 2475 |
| 7.50-15 | 6.00/6.50 | 774 | 200 | 4360 | 3490 | 4050 | 3040 | 3775 | 2835 | 2890 |
| 21*8-9 | 6.00 | 535 | 189 | 2810 | 2250 | 2715 | 2035 | 2530 | 1895 | 1940 |
| 23*9-10 | 6.50 | 595 | 211 | 3420 | 2735 | 3300 | 2475 | 3075 | 2305 | 2355 |
| 28*9-15 | 7.00 | 690 | 200 | 4090 | 3270 | 3945 | 2960 | 3675 | 2755 | 2050 |
| 8.25-12 | 5.00 | 690 | 180 | 3325 | 2660 | 3215 | 2410 | 2995 | 2245 | 2295 |
| 8.25-15 | 6.50 | 805 | 195 | 4940 | 3950 | 4765 | 3575 | 4440 | 3330 | 3405 |
| 3.00-15 | 8.00 | 780 | 236 | 5990 | 4790 | 5780 | 4335 | 5380 | 4035 | 4130 |
| 7.50-16 | 8.00 | 785 | 170 | 7800 | 5850 | 7080 | 5310 | 6100 | 4500 | 6400 |

Contact Us:

cherry@dehort.com

Devote ourselves to give you best Tyre and Rim solution.

Cherry Quin General Manager

DEBORT CO., LIMITED

Email: cherry@dehort.com
 Tel: 0086-532-80991938
 Web: www.dehort.com
 Address: 2-3010, No.222 Shenzhen Road, Qingdao, China.

Cellphone : 0086-18660256278
 Fax: 0086-532-80990998
 Skype: cherryqueenchina

HIGH QUALITY TIMELY DELIVERY PERFECT SERVICE